

PISTON AND RING SPECIFICATIONS

Year	VIN	No. Cylinder Displacement cu. in. (liter)	Piston Clearance	Ring Gap			Ring Side Clearance		
				Top	Bottom	Oil	Top	Bottom	Oil
				Compression	Compression	Control	Compression	Compression	Control
1985	N	6-260 (4.3)	0.0007- 0.0017	0.0100- 0.0250	0.0100- 0.0250	0.0150- 0.0550	0.0012- 0.0032	0.0012- 0.0032	0.0020- 0.0070
	T	6-292 (4.8)	0.0026- 0.0036	0.0100- 0.0200	0.0100- 0.0200	0.0150- 0.0550	0.0120- 0.0027	0.0020- 0.0040	0.0005- 0.0055
	F	8-305 (5.0)	0.0007- 0.0017	0.0100- 0.0200	0.0100- 0.0250	0.0150- 0.0550	0.0012- 0.0032	0.0012- 0.0032	0.0020- 0.0070
	H	8-305 (5.0)	0.0007- 0.0017	0.0100- 0.0200	0.0100- 0.0250	0.0150- 0.0550	0.0012- 0.0032	0.0012- 0.0032	0.0020- 0.0070
	L	8-350 (5.7)	0.0007- 0.0017	0.0100- 0.0200	0.0130- 0.0250	0.0150- 0.0550	0.0012- 0.0032	0.0012- 0.0032	0.0020- 0.0070
	M	8-350 (5.7)	0.0007- 0.0017	0.0100- 0.0200	0.0130- 0.0250	0.0150- 0.0550	0.0012- 0.0032	0.0012- 0.0032	0.0020- 0.0070
	C	8-379 (6.2)	①	0.0120- 0.0220	0.0300- 0.0400	0.0100- 0.0210	0.0030- 0.0071	0.0300- 0.0400	0.0016- 0.0038
	J	8-379 (6.2)	①	0.0120- 0.0220	0.0300- 0.0400	0.0100- 0.0210	0.0030- 0.0071	0.0300- 0.0400	0.0016- 0.0038
	W	8-454 (7.4)	0.0030- 0.0040	0.0100- 0.0200	0.0100- 0.0200	0.0150- 0.0550	0.0017- 0.0032	0.0017- 0.0032	0.0050- 0.0065
1986	N	6-260 (4.3)	0.0007- 0.0017	0.0100- 0.0250	0.0100- 0.0250	0.0150- 0.0550	0.0012- 0.0032	0.0012- 0.0032	0.0020- 0.0070
	Z	6-260 (4.3)	0.0007- 0.0017	0.0100- 0.0250	0.0100- 0.0250	0.0150- 0.0550	0.0012- 0.0032	0.0012- 0.0032	0.0020- 0.0070
	T	6-292 (4.8)	0.0026- 0.0036	0.0100- 0.0200	0.0100- 0.0200	0.0150- 0.0550	0.0120- 0.0027	0.0020- 0.0040	0.0005- 0.0055
	F	8-305 (5.0)	0.0007- 0.0017	0.0100- 0.0200	0.0100- 0.0250	0.0150- 0.0550	0.0012- 0.0032	0.0012- 0.0032	0.0020- 0.0070
	H	8-305 (5.0)	0.0007- 0.0017	0.0100- 0.0200	0.0100- 0.0250	0.0150- 0.0550	0.0012- 0.0032	0.0012- 0.0032	0.0020- 0.0070
	L	8-350 (5.7)	0.0007- 0.0017	0.0100- 0.0200	0.0130- 0.0250	0.0150- 0.0550	0.0012- 0.0032	0.0012- 0.0032	0.0020- 0.0070
	M	8-350 (5.7)	0.0007- 0.0017	0.0100- 0.0200	0.0130- 0.0250	0.0150- 0.0550	0.0012- 0.0032	0.0012- 0.0032	0.0020- 0.0070
	C	8-379 (6.2)	①	0.0120- 0.0220	0.0300- 0.0400	0.0100- 0.0210	0.0030- 0.0071	0.0300- 0.0400	0.0016- 0.0038
	J	8-379 (6.2)	①	0.0120- 0.0220	0.0300- 0.0400	0.0100- 0.0210	0.0030- 0.0071	0.0300- 0.0400	0.0016- 0.0038
	W	8-454 (7.4)	0.0030- 0.0040	0.0100- 0.0200	0.0100- 0.0200	0.0150- 0.0550	0.0017- 0.0032	0.0017- 0.0032	0.0050- 0.0065